



Click on www.xprinter.net
to learn more.
<http://www.xprinter.net>
Service hotline: 4006-139-828



MINI RECEIPT PRINTER PRODUCT CATALOG

Xprinter



Innovation and
Technology

Provide you with the best
solution for receipt printer

ZHUHAI J-SPEED TECHNOLOGY CO., LTD.

Add: 4th Floor, 2 Building, Stone Industrial Park,
Qianshan, Zhuhai City, Guangdong Province, China
Tel: 86-756-3895786 Fax: 86-756-3895720
E-mail: x-printers@foxmail.com ruth@xprinter.net

<http://www.xprinter.net>

WE ARE FOCUS ON
PRODUCING GOOD
QUALITY POS
PRINTERS AND

Xprinter Mini Receipt Printer Global brands

Zhuhai J-Speed Technology Co., Ltd. is located in Qianshan Hi-tech Industrial Park, Zhuhai coast city in Guangdong province of China. It is a professional enterprise who R&D, manufacture, market and service mini printers. It has professional technology and perfect management, and a great combination of innovative technicians. It is a leading manufacturer in the industry. Our products passed CCC, CE, FCC, ROHS, ISO9001 CB BIS quality system examination

We provide OEM/ODM for a lot of international customers and are highly responsible for every customer. We adhere to put the market requirement at first, the technical innovation as the driving force of the operational concept, develop and manufacture all kinds of mini printers. It widely used in supermarket, banks, telecommunications, catering and other industries. We provide the best products option not only from the designing to manufacture, but also from appearance to performance.

We have experienced senior technicians who major in technology development, they are the accelerator of your success who can provide the best after-service for you. We are looking forward the win-win cooperation.

Xprinter

Provide you with the
best solution for
receipt printer

XP-T58NC

Thermal Receipt Printer

Key features

- Big gear printing head
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Support Chinese GB18030
- Avoid order missing
- Support simplified/traditional Chinese, Japanese, Korean and many other international Languages



Specifications

Model	XP-T58NC
Printing method	Direct thermal
Printing speed	90mm/s
Paper width	57.5 ± 0.5mm
Roll paper	65mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A
Interface	Parallel/Serial/USB/Lan
Auto cutter	Full or partial (optional)
Reliability	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.05 kg
Dimension	190 × 135 × 125.5mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-T58K

Thermal Receipt Printer

Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Support Chinese GB18030
- Avoid order missing
- Compatible with ESC/POS commands



Specifications

Model	XP-T58K
Printing method	Direct thermal
Printing speed	120mm/s
Paper width	57.5 ± 0.5mm
Roll paper	65mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A
Interface	Parallel/Serial/USB/Lan
Auto cutter	---
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.10 kg
Dimension	199 × 132 × 111.5mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-T58KC

Thermal Receipt Printer

Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support Linux & Windows system
- Support OPOS driver
- Support Chinese GB18030
- Avoid order missing
- Compatible with ESC/POS commands



Specifications

Model	XP-T58KC
Printing method	Direct thermal
Printing speed	120mm/s
Paper width	57.5 ± 0.5mm
Roll paper	65mm
Paper thickness	0.06~0.08mm
Column capacity	384 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	64K Bytes
Input buffer	32K Bytes
Power supply	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A
Interface	Parallel/Serial/USB/Lan
Auto cutter	Full or partial (optional)
Reliability	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.10 kg
Dimension	199 × 132 × 111.5mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

POS Printer



Specifications

Model	XP-58III	XP-58IIIK	XP-58IIIA
POS Printer			
Printing speed	90mm/s	90mm/s	90mm/s
Column capacity	384 dots/line	384 dots/line	384 dots/line
Interface	Parallel/Serial/USB/Lan	Parallel/Serial/USB	Parallel/USB
NV FLASH	64K Bytes	64K Bytes	64K Bytes
Input buffer	32K Bytes	32K Bytes	32K Bytes
Auto cutter	---	---	---
Power supply	DC 12V = 2.6A	DC 12V = 2.6A	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A	DC 12V = 1A	DC 12V = 1A
Gross weight	0.94 kg	0.73 kg	0.82 kg
Reliability	Printing head life: 50 km	Printing head life: 50 km	Printing head life: 50 km
Dimension	235 × 145 × 125mm (D × W × H)	188 × 132 × 112mm (D × W × H)	215 × 135 × 107mm (D × W × H)

Specifications

Model	XP-T58K	XP-T58KC	XP-T58NC
POS Printer			
Printing speed	120mm/s	120mm/s	90mm/s
Column capacity	384 dots/line	384 dots/line	384 dots/line
Interface	Parallel/Serial/USB/Lan	Parallel/Serial/USB/Lan	Parallel/Serial/USB/Lan
NV FLASH	64K Bytes	64K Bytes	64K Bytes
Input buffer	32K Bytes	32K Bytes	32K Bytes
Auto cutter	---	Full or partial (option)	Full or partial (option)
Power supply	DC 12V = 2.6A	DC 12V = 2.6A	DC 12V = 2.6A
Cash drawer control	DC 12V = 1A	DC 12V = 1A	DC 12V = 1A
Gross weight	1.10 kg	1.10 kg	1.05 kg
Reliability	Printing head life: 50 km	Printing head life: 50 km Auto cutter life: 500 thousand cuts	Printing head life: 50 km Auto cutter life: 500 thousand cuts
Dimension	199 × 132 × 111.5mm (D × W × H)	199 × 132 × 111.5mm (D × W × H)	190 × 135 × 125.5mm (D × W × H)

XP-F76E / F76EC

Impact Dot Matrix Printer

Key features

- Traditional Chinese and simplified Chinese switched by command
- Easy paper loading
- Bi-directional, two color printing
- Three-ply capable
- Citizen DP332 printing head



Specifications

Model	XP-F76E	XP-F76EC
Printing method	9-Pin serial impact dot-matrix printing	
Printing speed	4.5 line/sec	
Paper width	75.5 ± 0.5mm	
Roll paper	65mm	
Paper thickness	0.06~0.08mm	
Column capacity	400 dots/line	
Line space	4.23mm (changeable using commands)	
Character size	ANK, Font A: 9×9 dots Font B: 7×9 dots Simplified/traditional Chinese: 16×16 dots	
Black mark detection	Support	
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)	
Input buffer	64 K Bytes	
Power supply	DC 24V ≐ 2.5A	
Cash drawer control	DC 24V ≐ 1A	
Interface	Serial+USB+Lan/WIFI/Bluetooth	
Auto cutter	---	
Reliability	Printing head life: 10 Million Lines	Printing head life: 10 Million Lines Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)	
Storage environment	Temperature (-10~60°C), humidity(10~90%)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux	
Command	Compatible with ESC/POS	
Gross weight	2.2 kg	2.3 kg
Dimension	247 × 156 × 143mm (D × W × H)	

Copyright © Zuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-T76K

Impact Dot Matrix Printer

Key features

- Dot matrix printer specially design for perforated paper
- Widely used in payment by credit, telecommunication or mobile ticket printing
- Paper end and printing head overheated sensor
- Support GB18030



Specifications

Model	XP-T76K
Printing method	9-Pin serial impact dot-matrix printing
Printing speed	4.5 line/sec
Paper width	75.5 ± 0.5mm
Roll paper	65mm
Paper thickness	0.06~0.08mm
Column capacity	300 dots/line
Line space	4.23mm (changeable using commands)
Character size	ANK, Font A: 9×9 dots Font B: 7×9 dots Simplified/traditional Chinese: 16×16 dots
Black mark detection	Support
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
Input buffer	64 K Bytes
Power supply	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A
Interface	Parallel/Serial/USB
Auto cutter	---
Reliability	Printing head life: 10 Million Lines
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.08 kg
Dimension	306 × 144 × 125mm (D × W × H)

Copyright © Zuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-76IINC

Impact Dot Matrix Printer

Key features

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



Specifications


Model	XP-76IINC
Printing method	9-Pin serial impact dot-matrix printing
Printing speed	4.5 line/sec
Paper width	75.5 ± 0.5mm
Roll paper	65mm
Paper thickness	0.06~0.08mm
Column capacity	400 dots/line
Line space	4.23mm (changeable using commands)
Character size	ANK, Font A: 9×9 dots Font B: 7×9 dots Simplified/traditional Chinese: 16×16 dots
Black mark detection	Support
Code page	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
Input buffer	64 K Bytes
Power supply	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A
Interface	Parallel/Serial/Lan/USB
Auto cutter	Full or partial (optional)
Reliability	Printing head life: 10 Million Lines Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux
Command	Compatible with ESC/POS
Gross weight	1.28 kg
Dimension	220 × 150 × 140mm (D × W × H)

Copyright © Zuhai J-speed Technology Co., Ltd. All Rights Reserved





Dot Matrix Printer



Specifications

Model	XP-76II+C	XP-7645III	XP-F76E
			
Printing speed	4.5 line/sec	4.5 line/sec	4.5 line/sec
Column capacity	400 dots/line	400 dots/line	400 dots/line
Interface	Parallel/Serial/USB/Lan	Parallel/Serial/USB/Lan	Serial+USB+Lan/WIFI/Bluetooth
Black mark detection	Support	Support	Support
Input buffer	64K Bytes	64K Bytes	64K Bytes
Auto cutter	Full or partial is optional	---	---
Power supply	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A	DC 24V ≐ 1A	DC 24V ≐ 1A
Gross weight	1.36 kg	1.36 kg	2.2 kg
Reliability	Printing head life: 10 Million Lines Auto Cutter Life: 1 million cuts	Printing head life: 10 Million Lines	Printing head life: 10 Million Lines
Dimension	230 × 146 × 145mm (D × W × H)	230 × 150 × 130mm (D × W × H)	247 × 156 × 143mm (D × W × H)

Specifications

Model	XP-F76EC	XP-T76K	XP-76IINC
			
Printing speed	4.5 line/sec	4.5 line/sec	4.5 line/sec
Column capacity	400 dots/line	300 dots/line	400 dots/line
Interface	Serial+USB+Lan/WIFI/Bluetooth	Parallel/Serial/USB/Lan	Parallel/Serial/USB/Lan
Black mark detection	Support	Support	Support
Input buffer	64K Bytes	64K Bytes	64K Bytes
Auto cutter	Full or partial is optional	---	Full or partial is optional
Power supply	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A	DC 24V ≐ 1A	DC 24V ≐ 1A
Gross weight	2.3 kg	1.08 kg	1.28 kg
Reliability	Printing head life: 10 Million Lines Auto Cutter Life: 1 million cuts	Printing head life: 10 Million Lines	Printing head life: 10 Million Lines
Dimension	247 × 156 × 143mm (D × W × H)	306 × 144 × 125mm (D × W × H)	220 × 150 × 140mm (D × W × H)

XP-D600

Thermal Receipt Printer

Key features

- Support QR CODE Printing
- 300mm / sec Max. printing speed
- USB+Serial+Lan interfaces together
- Support wall mountable and truck cable
- Change IP through Web or Serial port
- Support Linux, Win 8.1 system
- Support 58/80mm paper roll printing



Specifications

Model	XP-D600
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	57.5 ± 0.5mm 79.5 ± 0.5mm
Roll paper	58mm 80mm
Paper thickness	0.06-0.08mm
Column capacity	384mm dots/ line (58mm) 576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.45 kg
Dimension	194.5 × 145 × 147mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-T230H / T260H

Thermal Receipt Printer

Key features

- Support QR CODE Printing
- Support Chinese GB18030
- 100MB Ethernet interface connection
- Avoid order missing
- Support black mark orientation
- Support oertype function
- Support 256K bytes NV logo download store and print



Specifications

Model	XP-T230H	XP-T260H
Printing method	Direct thermal	
Printing speed	230mm/s	260mm/s
Paper width	79.5 ± 0.5mm	
Roll paper	80mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm (changeable using commands)	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE	
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)	
NV FLASH	256K Bytes	
Input buffer	64K Bytes	2048K Bytes
Power supply	DC 24V ± 2.5A	
Cash drawer control	DC 24V ± 1A	
Interface	Parallel/USB+Serial/Lan	Serial+USB+Lan
Auto cutter	Full/Partial(optional)	
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts	
Working environment	Temperature (0~45°C), humidity(10~80%)	
Storage environment	Temperature (-10~60°C), humidity(10~90%)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS	
Command	Compatible with ESC/POS	
Gross weight	1.4 kg	
Dimension	195 × 140 × 143mm (D × W × H)	

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-T260M

Front Paper Out Printer

Key features

- Front paper loading
- Support QR code printing
- Serial+USB+Lan interface
- Eight levels for printing density
- Support 2048KB input buffer



Specifications

Model	XP-T260M
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	79.5 ± 0.5mm
Roll paper	80mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.48 kg
Dimension	185 × 140 × 134mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-D300M

Front Paper Loading Printer

Key features

- Support QR CODE Printing
- 300mm/s high speed printing
- Serial+USB+Lan interface
- Vertical printing, desktop printing or Internet printing
- Support 58/80mm paper roll printing



Specifications

Model	XP-D300M
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	57.5 ± 0.5mm 79.5 ± 0.5mm
Roll paper	58mm 80mm
Paper thickness	0.06-0.08mm
Column capacity	384mm dots/ line (58mm) 576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.44 kg
Dimension	144.5 × 146 × 188.5mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-D300K

Thermal Receipt Printer

Key features

- Support QR CODE Printing
- Support Serial+USB+Lan interfaces
- Support 58/80mm paper roll printing
- Printer head life is 100km, 1 million cuts



Specifications

Model	XP-D300K
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	79.5 ± 0.5mm
Roll paper	80mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.26 kg
Dimension	190 × 145 × 143mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-C230N / C260N

Thermal Receipt Printer

Key features

- Support QR CODE printing (XP-C260N)
- Support Chinese GB18030
- 100MB Ethernet interface connection
- Avoid order missing
- Support black mark orientation
- Support overtype function
- Input buffer 2048K bytes (XP-C260N)



Specifications

Model	XP-C230N	XP-C260N
Printing method	Direct thermal	
Printing speed	230mm/s	260mm/s
Paper width	79.5 ± 0.5mm	
Roll paper	80mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm (changeable using commands)	
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE	
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)	
NV FLASH	256K Bytes	
Input buffer	64K Bytes	2048K Bytes
Power supply	DC 24V ± 2.5A	
Cash drawer control	DC 24V ± 1A	
Interface	Parallel/USB+Serial/Lan	Serial+USB+Lan
Auto cutter	Full/Partial(optional)	
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts	
Working environment	Temperature (0~45°C), humidity(10~80%)	
Storage environment	Temperature (-10~60°C), humidity(10~90%)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS	
Command	Compatible with ESC/POS	
Gross weight	1.5 kg	
Dimension	190 × 145 × 138mm (L × W × H)	

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-C2008

Thermal Receipt Printer

Key features

- Easy paper loading
- Waterproof, oil proof, dustproof design
- Serial+USB+Lan, USB+Wifi interface
- Support kitchen printing and trunk cable
- Full/Partial optional, no paper jamming problem



Specifications

Model	XP-C2008
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 ± 0.5mm
Roll paper	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ± 2.5A
Cash drawer control	DC 24V ± 1A
Interface	Serial+USB+Lan, USB+Wifi
Auto cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.70 kg
Dimension	190 × 145 × 150mm (D × W × H)

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-360B

Thermal Barcode Printer

Key features

- Min 50.8mm/s / Max 127mm/s
- Built-in power supply
- Memory: DRAM: 4M, NV FLASH: 4M
- Support PDF417, QR CODE, DATMATRIX
- Support to modify IP address through browser
- 100MB Ethernet interface connection



Specifications

Model	XP-360B
Printing method	Direct thermal
Resolution	203dpi
Printing width	76mm
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)
Print head temperature sensor	Thermal sensitive resistance
Print head position sensor	Micro switch
Media type	Paper roll, sticker, label fold, etc.
Bar code	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14
QR CODE	PDF417、QR CODE、Data Matrix
Roll paper	MIN 25mm
Paper off type	Tear off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270° rotation
Gross weight	1.42 kg
Dimension	212.4(D) x 143(W) x 145.5(H)mm
Work	5~45°C, 20~80%RH
Storage	-40~55°C, ≤93%RH(40°C)
Input	24VDC, 2.5A
Paper exists detection	Photoelectric sensor
Interface	USB
Memory	DRAM: 4M; FLASH: 4M
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved

XP-350BM

Thermal Barcode Printer

Key features

- Printing speed: Min 50.8mm/s, Max 127mm/s
- Paper width: 80mm
- Thermal sensitive resistance, photoelectric sensor
- Serial+USB+Lan interface
- Labels peel off, tear off automatically
- Memory: DRAM: 4M NV FLASH: 4M
- Support PDF417, QR CODE, Data matrix 2D Printing
- Embedded with internet default IP
- 100MB Ethernet interface connection, data transfer efficiency



Specifications



Model	XP-350BM
Printing method	Direct thermal
Resolution	203dpi (8dots/mm)
Printing width	16~82mm
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)
Print head temperature sensor	Thermal sensitive resistance
Print head position sensor	Micro switch
Media type	Paper roll, sticker, label fold, etc.
Bar code	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14
QR CODE	PDF417、QR CODE、Data Matrix
Roll paper	80mm (Max.), External roll paper (unlimited)
Paper off type	Tear off & peel off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270° rotation
Gross weight	1.44 kg
Dimension	220(D) x 148(W) x 150(H)mm
Work	5~45°C, 20~80%RH
Storage	-40~55°C, ≤93%RH(40°C)
Input	24VDC, 2.5A
Paper exists detection	Photoelectric sensor
Interface	Serial+USB+LAN
Memory	DRAM: 4M; FLASH: 4M
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM

Copyright © Zhuhai J-speed Technology Co., Ltd. All Rights Reserved



POS Printer

XP-80mm Thermal Receipt Printer L

Specifications

Model	XP-C230 / C260K	XP-C2008
POS Printer		
Printing speed	230mm/s 260mm/s	260mm/s
Column capacity	576 dots/line 512 dots/line	576 dots/line 512 dots/line
Interface	Parallel/Serail+USB/Lan Parallel+USB/Serail+USB+Lan	Serial+USB+Lan, USB+Wifi
NV FLASH	256K Bytes	256K Bytes
Input buffer	64K Bytes 2048K Bytes	2048K Bytes
Auto cutter	Full or partial is optional	Full or partial is optional
Power supply	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A	DC 24V ≐ 1A
Gross weight	1.52 kg	1.70 kg
Reliability	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts
Dimension	200 × 140 × 140mm (D × W × H)	190 × 145 × 150mm (D × W × H)





Specifications


Model	XP-C260H	XP-C230N / C260N
POS Printer		
Printing speed	260mm/s	230mm/s 260mm/s
Column capacity	576 dots/line 512 dots/line	576 dots/line 512 dots/line
Interface	Parallel+USB/Serail+USB+Lan	Parallel/Serail+USB Parallel+USB/Serail+USB+Lan
NV FLASH	256K Bytes	256K Bytes
Input buffer	2048K Bytes	64K Bytes 2048K Bytes
Auto cutter	Full or partial is optional	Full or partial is optional
Power supply	DC 24V ≐ 2.5A	DC 24V ≐ 2.5A
Cash drawer control	DC 24V ≐ 1A	DC 24V ≐ 1A
Gross weight	1.70 kg	1.5 kg
Reliability	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts
Dimension	198 × 148 × 138mm (D × W × H)	190 × 145 × 138mm (D × W × H)

POS Printer

XP-80mm Thermal Receipt Printer

Specifications




Model	XP-F900+	XP-T260M	XP-T230H / T260H
 POS Printer			
Printing speed	260mm/s	300mm/s	230mm/s 260mm/s
Column capacity	576 dots/line 512 dots/line	576 dots/line 512 dots/line	576 dots/line 512 dots/line
Interface	Serial+USB+Lan	Serial+USB+Lan	Parallel/Serial+USB/Lan Serial+USB+Lan
NV FLASH	256K Bytes	256K Bytes	256K Bytes
Input buffer	2048K Bytes	2048K Bytes	64K Bytes 2048K Bytes
Auto cutter	Full or partial is optional	Full or partial is optional	Full or partial is optional
Power supply	DC 24V \approx 2.5A	DC 24V \approx 2.5A	DC 24V \approx 2.5A
Cash drawer control	DC 24V \approx 1A	DC 24V \approx 1A	DC 24V \approx 1A
Gross weight	1.65 kg	1.48 kg	1.4 kg
Reliability	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts
Dimension	188 x 145 x 148mm (D x W x H)	185 x 140 x 134mm (D x W x H)	195 x 140 x 143mm (D x W x H)

Model	XP-D300K	XP-D300M	XP-D600
 POS Printer			
Printing speed	300mm/s	300mm/s	300mm/s
Column capacity	576 dots/line 512 dots/line	576 dots/line 512 dots/line	576 dots/line 512 dots/line
Interface	Serial+USB+Lan	Serial+USB+Lan	Serial+USB+Lan
NV FLASH	256K Bytes	256K Bytes	256K Bytes
Input buffer	2048K Bytes	2048K Bytes	2048K Bytes
Auto cutter	Full or partial is optional	Full or partial is optional	Full or partial is optional
Power supply	DC 24V \approx 2.5A	DC 24V \approx 2.5A	DC 24V \approx 2.5A
Cash drawer control	DC 24V \approx 1A	DC 24V \approx 1A	DC 24V \approx 1A
Gross weight	1.26 kg	1.44 kg	1.45 kg
Reliability	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts	Printing head life: 100 km Auto Cutter Life: 1 million cuts
Dimension	190 x 145 x 143mm (D x W x H)	144.5 x 146 x 188.5mm (D x W x H)	194.5 x 145 x 147mm (D x W x H)




Barcode Printer



Specifications

Model	XP-233B	XP-330B
 POS Printer		
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)	127mm/s. (Max.); 50.8mm/s. (Min.)
Column capacity	203dpi (8dots/mm)	203dpi (8dots/mm)
Interface	USB	Parallel/Serial/USB/Lan
NV FLASH	4 M	2 M
Input buffer	4 M	2 M
Auto cutter	---	---
Power supply	DC 24V \approx 4A	DC 24V \approx 2.5A
Cash drawer control	DC 12V \approx 1A	DC 24V \approx 1A
Gross weight	1.04 kg	1.5 kg
Reliability	Printing head life: 100 km	Printing head life: 100 km
Dimension	190 x 135 x 137mm (D x W x H)	216 x 142 x 130mm (D x W x H)

Specifications

Model	XP-350BM	XP-360B
 Barcode Printer		
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)	127mm/s. (Max.); 50.8mm/s. (Min.)
Resolution	203dpi (8dots/mm)	203dpi (8dots/mm)
Interface	Serial+USB+Lan	USB
NV FLASH	4 M	4 M
Input buffer	4 M	4 M
Auto cutter	---	---
Power supply	DC 24V \approx 2.5A	DC 24V \approx 2.5A
Cash drawer control	DC 24V \approx 1A	DC 24V \approx 1A
Gross weight	1.44 kg	1.42 kg
Reliability	Printing head life: 100 km	Printing head life: 100 km
Dimension	220 x 148 x 150mm (D x W x H)	212.4 x 143 x 145.5mm (D x W x H)